



Zoom In

**Name of Product** COMNET-8800

**Description**

Next Generation CD for Global Banks

Ask Through E-Mail

**Contact Point and Number**  
 ■ Joon Suk Oh/manager, Global Business Division  
 ■ E-mail : jsoh@chunghocomnet.com

**Specifications**

Item	Item Detail	Standard Specifications	Notes
Outer Dimension	Front Access Model	506 mm(W)×1433 mm(H)×845 mm(D)	
	Rear Access Model	506 mm(W)×1433 mm(H)×845 mm(D)	
	Include TTW	626 mm(W)×1900 mm(H)×1038 mm(D)	
Weight	Machine	Approx. 450 kg, 4-cartridge CDU, excluding options, bill and media	
	TTW UNIT	Approx. 35kg	
Operation Direction	Lobby type	Front loader or Rear loader (specified on ordering)	
	TTW type	Rear loader only	
Cabinet	Fasia	Polymer Fascia	
	Safety	UL 291 24-hour Level 1	
	Lock	Combination Lock (Option : Long Key Lock or Electric Lock)	
TTW Bezel		Steel bezel (up to 203 mm of wall thickness)	
Power	Input Voltage	AC100-120V / 200-240V (Select at power supply)	
	Input Frequency	50±2 Hz or 60±2 Hz	
	Power Consumption	Less than 350 Watts	

	UPS	Not provided	Option
Consumer Interface	Display Resolution Privacy Shield Touch Screen Key Entry Pin Pad Guidance Indicators	15.0 inch color TFT 15.0 inch : 1024 x 768 dots Not provided Not provided 4 keys each on the left and right side of TFT 16-Key Encryption Pin Pad 3 indicators (card, receipt and bill)	Option Option (IR Type) PCI 2.X approval
Operator Panel	Display Resolution Interface	8.0 inch color TFT 8.0 inch : 800 x 600 dots Resistor 8" Touch screen (USB)	Rear loader Only
PC	Mother Board  CPU Memory HDD Media Power Supply	Size : Micro ATX form factor Chipset : Intel H61 Chipset CPU Scket : LGA1155 Memory : Dual CH DDR3 SDRAM Max 4G LAN : 2*Onboard Audio : Onboard Video : Onboard (2 CH, DVI Port not use) USB : 4*Rear Panel, 3*Connector Serial : 1*Rear Panel, 9*Connectors Expansion slot : 1*PCIe×16, 1*PCIe×1, 2*PCI More than Intel Pentium G2120(2 Cores, 3.10 GHz) 1*DDR3 2G More than 500G DVD-Multi 300W ATX POWER, Input: 100-240V / Load: 300W	
Card Reader	Type MS IC ETC Function	MCRW MS Card Reader/Writer (ISO 7810,7811 Track1,2,3) Hico/Loco CapableF2F Reading Method IC Card Reader/Writer (ISO 7816) EMV2000 Level1,2 approval, PBOC2.0 Level1,2 approval Card returned on power failure Warped Cards support Anti-Skimming function support	
Cash Dispenser Unit	Type Support note size Bunch size	Presenter type Short 60~82mm, Long 120~172mm Max 60 notes by transaction	

	Cassette	Up to 4 Cassettes, Dispense Max 3,000 notes by cassette
	Count Speed	6 notes/sec
	Reject Box	Integrated in 1st Cassette, Capacity Approx 150 Bills
	Shutter	Provided
Receipt Printer	Print Method	Direct Thermal Line Printer
	Print speed	max 150mm/sec
	Paper width	80mm
	paper setting	Semi auto paper setting
	presenter	Half presenter (Loop type)
	Black mark	Support
	Paper capacity	5,000 transaction or 2,000 transaction
Journal Printer (Option)	Print Method	Direct Thermal Line Printer
	Print speed	Print speed : max 150mm/sec
	Paper width	Paper width : 80mm
	paper setting	Manual paper setting
	Paper capacity	5,000 transaction
ETC Option	Barcode Reader	1D Barcode Reader
	RF Card Reader	Type A,B
	Earphone Jack	Software TTS ADA
	Customer Sensor	Detecting distance 100 Cm
	Camera	USB Camera (Face, Hand)
	Heater	300W or 1kW